

NAIL TAG

Transponder
Special Form

PART ID:
1034-01-152-00

Unique nail-shaped LF RFID Tag designed for use in wood.

Main Specifications

Material	Polyamid
Operating Temperature	-25°C to 85°C
IP Class	IP67
Compliance	RoHs & Reach, CE
Key Features	Rough Environment, Versatile, High Durability



Chip Specification (Chip 152)

Chip	EM Marin - EM4200/Unique
Frequency	125 kHz (LF)
Memory	UID 64 Bit; Read only
Norm	ISO/IEC 11784/85 Compatible

Full Specifications

Product ID	1034
Name	NAIL TAG
Material	Polyamid
Shape	Potted
Short Description	Unique nail-shaped LF RFID Tag designed for use in wood.
Long Description	The Nail Tag transponder makes tagging wood and other solid materials as easy as hitting a nail on the head. These unique tags are built for rugged treatment, featuring high resistance to moisture, vibration and shock.
Key Features	Rough Environment, Versatile, High Durability
Main Use	Tree/Pallet Identification
Article Type	Special Form
Color	Black
Diameter [mm]	4
Length [mm]	35.5
Weight [g]	0.7
Operating Temp °C (min)	-25

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Operating Temp °C (max)	85
Storage Temp °C (min)	-25
Storage Temp °C (max)	85
IP Class	IP67
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Plug-in
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1034-01-152-00	35x4mm	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible