Transponder Laundry TAG

PART ID: 1048-01-325-00

Latest generation of RAIN UHF thermal laundry patches with optimized reading distances and offering high level of flexibility and durability for laundry applications

Main Specifications

Material	Linen
Operating Temperature	-35°C to 95°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	High Durability, Ultra Thin, Heat Tolerant

Chip Specification (Chip 325)

Chip	EM Marin - EM4124		
Frequency	860~960 MHz (UHF)		
Memory			
Norm	ISO/IEC 18000-6C, EPC Class 1 Gen2, RAIN RFID		

Full Specifications

Product ID	1048		
Material	Linen		
Shape	Laminated		
Long Description	Latest generation of RAIN UHF thermal laundry patches with optimized reading distances and offering high level of flexibility and durability for laundry applications		
Key Features	High Durability, Ultra Thin, Heat Tolerant		
Comments	Reading Distance up to 6m on linen @ 868MHz (depends on Reader and Environment)		
Main Use	Garments, Hotel Linens		
Article Type	Laundry TAG		
Color	Brown		
Length [mm]	70		
Width [mm]	17		
Thickness [mm]	1		
Weight [g]	1.15		

e TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS

declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.



Due to unresolved patent issues

ECTUS

Operating Temp °C (min)	-35
Operating Temp °C (max)	95
Storage Temp °C (min)	-35
Storage Temp °C (max)	95
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Sew-in
Compliance	RoHs & Reach, CE

TECTUS

VARIANTS AND ICS

ID	Variant	Band	Туре	ISO
1048-01-325-00	70x17x1mm Heat Seal	UHF	EM4124	ISO/IEC 18000-6C, EPC Class 1 Gen2, RAIN RFID

*TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use
of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.
Where application information is given, it is only advisory and does not form part of the specification.

TECTUS Technology GmbH | Lustheide 85 | D-51427 Bergisch Gladbach | Phone: +49 (0) 22 04 976 88 0 | Fax: +49 (0) 22 04 976 88 10