

# Transponder DISC TAG

#### **PART ID:**

## 1063-02-269-00

Tiny HF RFID transponders for enclosure into virtually any form factor.

#### **Main Specifications**

Material	Ероху
Operating Temperature	-40°C to 85°C
IP Class	IP67
Compliance	RoHs & Reach, CE
Key Features	Small Size, Versatile, Cost- Effective, High Durability, Cryogenic resistance



## **Chip Specification (Chip 269)**

Chip	EM Marin - Vigo		
Frequency	13.56 MHz ( HF )		
Memory	1024 bit		
Norm	ISO 15693		

# **Full Specifications**

Product ID	1063		
Material	Ероху		
Shape	Potted		
Short Description	Tiny HF RFID transponders for enclosure into virtually any form factor.		
Long Description	Embeddable RFID transponders allow manufacturers to integrate HID Global electronic components seamlessly into tag designs optimized for any application. Small transponders are for space-constrained applications, our smallest disc-shaped units deliver high performance.		
Key Features	Small Size, Versatile, Cost-Effective, High Durability, Cryogenic resistance		
Main Use	Embeddable RFID		
Article Type	DISC TAG		
Color	Black		
Thickness [mm]	1		
Operating Temp °C (min)	-40		
Operating Temp °C (max)	85		
Storage Temp °C (min)	-40		

eTECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.



Storage Temp °C (max)	85
IP Class	IP67
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Embed
Compliance	RoHs & Reach, CE

## **VARIANTS AND ICS**

ID	Variant	Band	Туре	ISO
1063-01-267-00	D6x1mm	HF	MB89R118	ISO/IEC 15693 & 18000-3
1063-02-269-00	D9.5x1mm	HF	Vigo	ISO 15693

eTECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.