

Metal Frame Keyfob

Transponder Keyfob

PART ID:
1066-01-206-00

Metal Frame keyfob is a stylish, attractive and durable keyfob with a massive frame of polished stainless steel and the body is suitable for laser engraving and full color printing. Our METAL Frame keyfob is available with all common chip variations and combination

Main Specifications

Material	ABS
Operating Temperature	-40°C to 70°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Durable Housing, High Durability, Versatile
Options	Laser Engraving, Encoding, Dual Frequency On Request, Other Chips On Request



Chip Specification (Chip 206)

Chip	NXP - MIFARE Classic EV1 1K
Frequency	13.56 MHz (HF)
Memory	UID 4/7 Byte; User 1K Byte
Norm	ISO/IEC 14443A & 18000-3

Full Specifications

Product ID	1066
Name	Metal Frame Keyfob
Material	ABS
Shape	Overmolded
Long Description	Metal Frame keyfob is a stylish, attractive and durable keyfob with a massive frame of polished stainless steel and the body is suitable for laser engraving and full color printing. Our METAL Frame keyfob is available with all common chip variations and combination
Key Features	Durable Housing, High Durability, Versatile
Options	Laser Engraving, Encoding, Dual Frequency On Request, Other Chips On Request
Main Use	Access Control
Article Type	Keyfob

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Length [mm]	48.5
Width [mm]	38
Thickness [mm]	7
Weight [g]	11
Operating Temp °C (min)	-40
Operating Temp °C (max)	70
Storage Temp °C (min)	-40
Storage Temp °C (max)	70
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	UL 94 V0
Mechanical Resistance	Not Specified
Attachment Method	Key-Hanger
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1066-01-206-00	Blue	HF	MIFARE Classic EV1 1K	ISO/IEC 14443A & 18000-3
1066-01-148-00	Blue	LF	ATA5577	ISO/IEC 11784/85 Compatible
1066-02-206-00	Black	HF	MIFARE Classic EV1 1K	ISO/IEC 14443A & 18000-3
1066-02-148-00	Black	LF	ATA5577	ISO/IEC 11784/85 Compatible