

Metal Frame Keyfob

Transponder Keyfob

PART ID:

1066-01-148-00

Metal Frame keyfob is a stylish, attractive and durable keyfob with a massive frame of polished stainless steel and the body is suitable for laser engraving and full color printing. Our METAL Frame keyfob is available with all common chip variations and combination

Main Specifications

| | |
|-----------------------|--|
| Material | ABS |
| Operating Temperature | -40°C to 70°C |
| IP Class | IP68 |
| Compliance | RoHs & Reach, CE |
| Key Features | Durable Housing, High Durability, Versatile |
| Options | Laser Engraving, Encoding, Dual Frequency On Request, Other Chips On Request |



Chip Specification (Chip 148)

| | |
|-----------|-----------------------------|
| Chip | Atmel - ATA5577 |
| Frequency | 125 kHz (LF) |
| Memory | UID 2x32 Bit; User 363 Bit |
| Norm | ISO/IEC 11784/85 Compatible |

Full Specifications

| | |
|------------------|---|
| Product ID | 1066 |
| Name | Metal Frame Keyfob |
| Material | ABS |
| Shape | Overmolded |
| Long Description | Metal Frame keyfob is a stylish, attractive and durable keyfob with a massive frame of polished stainless steel and the body is suitable for laser engraving and full color printing. Our METAL Frame keyfob is available with all common chip variations and combination |
| Key Features | Durable Housing, High Durability, Versatile |
| Options | Laser Engraving, Encoding, Dual Frequency On Request, Other Chips On Request |
| Main Use | Access Control |
| Article Type | Keyfob |

©TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.

| | |
|-------------------------|------------------|
| Length [mm] | 48.5 |
| Width [mm] | 38 |
| Thickness [mm] | 7 |
| Weight [g] | 11 |
| Operating Temp °C (min) | -40 |
| Operating Temp °C (max) | 70 |
| Storage Temp °C (min) | -40 |
| Storage Temp °C (max) | 70 |
| IP Class | IP68 |
| Chemical Resistance | Not Specified |
| Flame Resistance | UL 94 V0 |
| Mechanical Resistance | Not Specified |
| Attachment Method | Key-Hanger |
| Compliance | RoHs & Reach, CE |

VARIANTS AND ICS

| ID | Variant | Band | Type | ISO |
|----------------|---------|------|-----------------------|-----------------------------|
| 1066-01-206-00 | Blue | HF | MIFARE Classic EV1 1K | ISO/IEC 14443A & 18000-3 |
| 1066-01-148-00 | Blue | LF | ATA5577 | ISO/IEC 11784/85 Compatible |
| 1066-02-206-00 | Black | HF | MIFARE Classic EV1 1K | ISO/IEC 14443A & 18000-3 |
| 1066-02-148-00 | Black | LF | ATA5577 | ISO/IEC 11784/85 Compatible |