

Transponder

DISC TAG


PART ID:

1077-01-105-00

The simple and conventional tag offers a quick and easy tagging function for asset management or process control.

Main Specifications

Material	ABS
Operating Temperature	-10°C to 50°C
IP Class	IP66
Compliance	RoHs & Reach, CE
Key Features	Durable Housing, Heat Tolerant, Cost-Effective
Options	Adhesive, Laser Engraving, Logo



Chip Specification (Chip 105)

Chip	NXP - HITAG 2
Frequency	125 kHz (LF)
Memory	UID 4 Byte; User 256 Bit
Norm	ISO/IEC 11784 & 11785

Full Specifications

Product ID	1077
Material	ABS
Shape	Ultrasonic Welded
Long Description	The simple and conventional tag offers a quick and easy tagging function for asset management or process control.
Key Features	Durable Housing, Heat Tolerant, Cost-Effective
Options	Adhesive, Laser Engraving, Logo
Article Type	DISC TAG
Color	Black
Diameter [mm]	30
Thickness [mm]	2.3
Hole	yes
Operating Temp °C (min)	-10
Operating Temp °C (max)	50

©TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Storage Temp °C (min)	-20
Storage Temp °C (max)	70
IP Class	IP66
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Screw/Rivet
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1077-01-105-00	D30x2.3mm, hole 3.3mm	LF	HITAG 2	ISO/IEC 11784 & 11785