

# Transponder

## PCB TAG


### PART ID:

# 1094

Overmolded PCB Tag is a hassle-free tag solution with both the antenna and chip in a small form factor which helps effortlessly add RFID function to electronic devices or small item with narrow space. More than that, the enhanced protection to the chip and antenna effectively guarantees its resistibility under harsh environment. Following ISO/IEC 15693 and NFC forum type 5 protocol, this tag enables a contactless communication between a device and NFC-enabled mobile phones via its RF interface.

### Main Specifications

Frequencies	LF HF UHF
Material	PCB
Operating Temperature	-40°C to 120°C
IP Class	IP67
Compliance	RoHs & REACH, FCC, CE
Key Features	Small Size, Tool Tracking, Ultra Thin



### Full Specifications

Product ID	1094
Material	PCB
Shape	Overmolded
Long Description	Overmolded PCB Tag is a hassle-free tag solution with both the antenna and chip in a small form factor which helps effortlessly add RFID function to electronic devices or small item with narrow space. More than that, the enhanced protection to the chip and antenna effectively guarantees its resistibility under harsh environment. Following ISO/IEC 15693 and NFC forum type 5 protocol, this tag enables a contactless communication between a device and NFC-enabled mobile phones via its RF interface.
Key Features	Small Size, Tool Tracking, Ultra Thin
Article Type	PCB TAG
Color	Black
Length [mm]	6.7
Width [mm]	6.7
Thickness [mm]	0.75
Operating Temp °C (min)	-40
Operating Temp °C (max)	120
Storage Temp °C (min)	-40
Storage Temp °C (max)	120

©TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.

IP Class	IP67
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Embed
Compliance	RoHs & REACH, FCC, CE

## VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1094-01-291-00	6.7x6.7x0.75mm	HF	ST25TV02K	ISO/IEC 15693 & 18000-3
1094-01-260-00	6.7x6.7x0.75mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3