

# Transponder

## Special Form

PART ID:

**1101-01-260-00**

Cable ties and more mounting elements up to 4.8mm width or D1.3mm

### Main Specifications

Material	Other
Operating Temperature	-40°C to 85°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Small Size, Tool Tracking, Versatile



### Chip Specification (Chip 260)

Chip	NXP - ICODE SLIX
Frequency	13.56 MHz ( HF )
Memory	UID 8 Byte; User 1024 Bit
Norm	ISO/IEC 15693 & 18000-3

## Full Specifications

Product ID	1101
Material	Other
Shape	Overmolded
Long Description	Cable ties and more mounting elements up to 4.8mm width or D1.3mm
Key Features	Small Size, Tool Tracking, Versatile
Main Use	Cable Tie
Article Type	Special Form
Color	Blue
Length [mm]	11.2
Width [mm]	5.15
Thickness [mm]	4.15
Weight [g]	0.26
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40

© 2025 TECTUS Technology GmbH. All rights reserved.

The content, design, and technical data of this specification are the intellectual property of TECTUS. TECTUS reserves the right to change any information or data in this document without prior notice. TECTUS declines all responsibility for the use of products with any other specifications, but the ones mentioned above. Any additional requirement for a specific customer application must be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

1/2

Storage Temp °C (max)	85
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Drop Test 1.8m
Attachment Method	Cable tie
Compliance	RoHs & Reach, CE

## VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1101-01-260-00	11.2x5.15x4.15mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3