

Transponder ON METAL

Ferrite TAG

PART ID:
2000-01-260-00

NFC Ferrite Tag is the smallest in the category to empower a device with NFC function. Designed to perform on metal, it is SMD process applicable to fit small parts.

Main Specifications

Material	Ferrite
Operating Temperature	-40°C to 85°C
IP Class	Not Specified
Compliance	RoHs & Reach, CE
Key Features	Small Size, ON-Metal Use, SMD-Applicable



Chip Specification (Chip 260)

Chip	NXP - ICODE SLIX
Frequency	13.56 MHz (HF)
Memory	UID 8 Byte; User 1024 Bit
Norm	ISO/IEC 15693 & 18000-3

Full Specifications

Product ID	2000
On Metal Use	yes
PEAK Performance	yes
Material	Ferrite
Shape	SMD Applicable
Long Description	NFC Ferrite Tag is the smallest in the category to empower a device with NFC function. Designed to perform on metal, it is SMD process applicable to fit small parts.
Key Features	Small Size, ON-Metal Use, SMD-Applicable
Comments	5x3mm Storage Temperature -55°C - +155°C
Article Type	Ferrite TAG
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-55
Storage Temp °C (max)	125
IP Class	Not Specified

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Embed
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2000-01-263-00	4.9x3x2.5mm	HF	NTAG213	ISO/IEC 14443A & 18000-3
2000-01-260-00	4.9x3x2.5mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
2000-02-260-00	4x2x2.5mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.