

Transponder ON METAL

Square TAG

PART ID:

2002-01-324-00

The Tag is designed to be read in the rear of a metallic object. It helps realize applications where a traditional metal tag sees a challenge. This tag is capable of reversing the interference caused by the metallic surface to become its steering power. The robust overmolded housing makes it ideal for industrial or logistics purpose. This tag sees no obstacles and makes front reading not the only choice. This transponder can be read both ON metal and BEHIND metal.



Main Specifications

| | |
|-----------------------|---|
| Material | Polyamid |
| Operating Temperature | -40°C to 85°C |
| IP Class | IP68 |
| Compliance | RoHs & Reach, CE |
| Key Features | Readable Behind Metal, Rough Environment, High Durability |
| Options | Adhesive, Pad Printing, Laser Engraving |

Chip Specification (Chip 324)

| | |
|-----------|----------------------------|
| Chip | NXP - UCODE 8 |
| Frequency | 860~960MHz (UHF) |
| Memory | TID 96 Bit; EPC 128 Bit |
| Norm | ISO 18000-6C / EPC Gen2 V2 |

Full Specifications

| | |
|------------------|--|
| Product ID | 2002 |
| On Metal Use | yes |
| PEAK Performance | yes |
| Material | Polyamid |
| Shape | Overmolded |
| Long Description | The Tag is designed to be read in the rear of a metallic object. It helps realize applications where a traditional metal tag sees a challenge. This tag is capable of reversing the interference caused by the metallic surface to become its steering power. The robust overmolded housing makes it ideal for industrial or logistics purpose. This tag sees no obstacles and makes front reading not the only choice. This transponder can be read both ON metal and BEHIND metal. |

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.

| | |
|-------------------------|---|
| Key Features | Readable Behind Metal, Rough Environment, High Durability |
| Options | Adhesive, Pad Printing, Laser Engraving |
| Article Type | Square TAG |
| Color | Yellow |
| Length [mm] | 52 |
| Width [mm] | 23 |
| Thickness [mm] | 5.7 |
| Weight [g] | 10 |
| Hole | yes |
| Operating Temp °C (min) | -40 |
| Operating Temp °C (max) | 85 |
| Storage Temp °C (min) | -40 |
| Storage Temp °C (max) | 125 |
| IP Class | IP68 |
| Chemical Resistance | Not Specified |
| Flame Resistance | Not Specified |
| Mechanical Resistance | Not Specified |
| Attachment Method | Screw/Rivet |
| Compliance | RoHs & Reach, CE |

VARIANTS AND ICS

| ID | Variant | Band | Type | ISO |
|----------------|-------------|------|---------|----------------------------|
| 2002-01-324-00 | 52x23x5.7mm | UHF | UCODE 8 | ISO 18000-6C / EPC Gen2 V2 |