

# Transponder ON METAL

## DISC TAG

### PART ID:

# 2004

Tag is made by overmolded process to elevate its grade to IP68. This type of tag features its small size.

### Main Specifications

Frequencies	<b>LF HF UHF</b>
Material	Polyamid
Operating Temperature	-25°C to 85°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	ON-Metal Use, Small Size, Durable Housing, Versatile, Heat Tolerant
Options	Adhesive, Laser Engraving, Pad Printing, Other Chips On Request



### Full Specifications

Product ID	2004
On Metal Use	yes
Material	Polyamid
Shape	Overmolded
Short Description	Tag is made by overmolded process to elevate its grade to IP68. This type of tag features its small size.
Long Description	Tag is made by overmolded process to elevate its grade to IP68. This type of tag features its small size.
Key Features	ON-Metal Use, Small Size, Durable Housing, Versatile, Heat Tolerant
Options	Adhesive, Laser Engraving, Pad Printing, Other Chips On Request
Main Use	Asset Tracking
Article Type	DISC TAG
Color	Black
Operating Temp °C (min)	-25
Operating Temp °C (max)	85
Storage Temp °C (min)	-25
Storage Temp °C (max)	120
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified

©TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Mechanical Resistance	Not Specified
Attachment Method	Glue
Compliance	RoHs & Reach, CE

## VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2004-01-260-00	D10x2.6mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
2004-02-260-00	D14.5x3mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3