

# Transponder ON METAL

## Square TAG

### PART ID:

**2007-01-264-00**

On-Metal Square Tag has a hard PVC substrate topped with soft Epoxy. With adhesive, it can be attached to any metallic surface.

### Main Specifications

Material	PVC
Operating Temperature	-25°C to 55°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	ON-Metal Use, Versatile, High Durability
Options	Offset Print, Other Chips On Request, Inkjet Print, Adhesive, Laser Engraving



### Chip Specification (Chip 264)

Chip	NXP - ICODE SLIX 2
Frequency	13.56 MHz ( HF )
Memory	UID 8 Byte; User 2528 Bit
Norm	ISO/IEC 15693 & 18000-3

### Full Specifications

Product ID	2007
On Metal Use	yes
Material	PVC
Shape	Laminated
Short Description	On-Metal Square Tag has a hard PVC substrate topped with soft Epoxy. With adhesive, it can be attached to any metallic surface.
Long Description	On-Metal Square Tag has a hard PVC substrate topped with soft Epoxy. With adhesive, it can be attached to any metallic surface.
Key Features	ON-Metal Use, Versatile, High Durability
Options	Offset Print, Other Chips On Request, Inkjet Print, Adhesive, Laser Engraving
Article Type	Square TAG
Color	White
Length [mm]	65

Width [mm]	25
Thickness [mm]	3.5
Operating Temp °C (min)	-25
Operating Temp °C (max)	55
Storage Temp °C (min)	-25
Storage Temp °C (max)	75
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Sticker
Compliance	RoHs & Reach, CE

## VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2007-01-263-00	65x25x3.5mm	HF	NTAG213	ISO/IEC 14443A & 18000-3
2007-01-264-00	65x25x3.5mm	HF	ICODE SLIX 2	ISO/IEC 15693 & 18000-3