

Transponder ON METAL

Square TAG

PART ID:

2007-01-260-00

On-Metal Square Tag has a hard PVC substrate topped with soft Epoxy. With adhesive, it can be attached to any metallic surface.

Main Specifications

Material	PVC
Operating Temperature	-25°C to 55°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	ON-Metal Use, Versatile, High Durability
Options	Offset Print, Other Chips On Request, Inkjet Print, Adhesive, Laser Engraving



Chip Specification (Chip 260)

Chip	NXP - ICODE SLIX
Frequency	13.56 MHz (HF)
Memory	UID 8 Byte; User 1024 Bit
Norm	ISO/IEC 15693 & 18000-3

Full Specifications

Product ID	2007
On Metal Use	yes
Material	PVC
Shape	Laminated
Short Description	On-Metal Square Tag has a hard PVC substrate topped with soft Epoxy. With adhesive, it can be attached to any metallic surface.
Long Description	On-Metal Square Tag has a hard PVC substrate topped with soft Epoxy. With adhesive, it can be attached to any metallic surface.
Key Features	ON-Metal Use, Versatile, High Durability
Options	Offset Print, Other Chips On Request, Inkjet Print, Adhesive, Laser Engraving
Article Type	Square TAG
Color	White
Length [mm]	65

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.

Width [mm]	25
Thickness [mm]	3.5
Operating Temp °C (min)	-25
Operating Temp °C (max)	55
Storage Temp °C (min)	-25
Storage Temp °C (max)	75
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Sticker
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2007-01-260-00	65x25x3.5mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
2007-01-263-00	65x25x3.5mm	HF	NTAG213	ISO/IEC 14443A & 18000-3