

# PLUG METAL TAG

## Transponder ON METAL Special Form

**PART ID:**  
**2008-02-260-00**

Make Identification Possible for Small Item

### Main Specifications

Material	Nylon Polymer
Operating Temperature	-40°C to 85°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Small Size, Versatile, High Durability, ON-Metal Use, IN-Metal Use

### Chip Specification (Chip 260)

Chip	NXP - ICODE SLIX
Frequency	13.56 MHz ( HF )
Memory	UID 8 Byte; User 1024 Bit
Norm	ISO/IEC 15693 & 18000-3



### Full Specifications

Product ID	2008
Name	PLUG METAL TAG
On Metal Use	yes
PEAK Performance	yes
Material	Nylon Polymer
Shape	Overmolded
Short Description	Make Identification Possible for Small Item
Long Description	Plug Metal Tag resembles a metric bolt (M7x4.0mm). This tag is designed to be screwed into a metallic object (taped with thread) and work with inductive couplers. Featuring the small tag size, It ideally goes to tool and equipment with small space, helping to provide the visibility and smart management in a production facility. Equipped with NXP I Code SLIX, this tag is compliant with ISO15693 and NFC forum

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.

	type 5 protocol.
Key Features	Small Size, Versatile, High Durability, ON-Metal Use, IN-Metal Use
Main Use	Machine or industrial equipment identification for asset management, Tool matching for process control
Article Type	Special Form
Color	Yellow
Diameter [mm]	6.8
Thickness [mm]	4
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	85
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Plug-in
Compliance	RoHs & Reach, CE

## VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2008-02-260-00	M7x4mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3