

PEAKID

Transponder ON METAL

Square TAG

PART ID:
2014-01-349-00

M-Crown tag operates effectively with good read range of over 15 meter when attached to metal.

Main Specifications

Material	ABS
Operating Temperature	-40°C to 85°C
IP Class	IP67
Compliance	RoHs & Reach, CE
Key Features	ON-Metal Use, Rough Environment, Heat Tolerant, Versatile, High Durability
Options	Color, Preprinted Artwork, Laser Engraving, Adhesive



Chip Specification (Chip 349)

Chip	Alien - Higgs 3
Frequency	869 MHz (UHF)
Memory	TID 64 Bit; EPC 96 Bit; User 512 Bit
Norm	ISO 18000-6C / EPC Gen2 V2

Full Specifications

Product ID	2014
Name	PEAKID
On Metal Use	yes
Material	ABS
Shape	Ultrasonic Welded
Short Description	M-Crown tag operates effectively with good read range of over 15 meter when attached to metal.
Long Description	M-Crown tag operates effectively with good read range of over 15 meter when attached to metal. Rugged construction for high durability. Can be attached by screws with the help of two holes. Can also be provided with Adhesive tape for easy attachment.
Key Features	ON-Metal Use, Rough Environment, Heat Tolerant, Versatile, High Durability
Options	Color, Preprinted Artwork, Laser Engraving, Adhesive
Article Type	Square TAG

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Color	Blue
Length [mm]	150
Width [mm]	25
Thickness [mm]	12
Weight [g]	25.8
Hole	yes
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	85
IP Class	IP67
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Screw/Rivet
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2014-01-349-00	150x25x12mm	UHF	Higgs 3	ISO 18000-6C / EPC Gen2 V2

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.