

Plug Tag Transponder ON METAL **Special Form**

PART ID:

2024-01-267-00

Main Specifications

Material	PC + GF
Operating Temperature	-25°C to 85°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Small Size, IN-Metal Use





Chip Specification (Chip 267)

Chip	Fujitsu - MB89R118
Frequency	13.56 MHz (HF)
Memory	UID 8 Byte; User 2K Byte FRAM
Norm	ISO/IEC 15693 & 18000-3

Full Specifications

Product ID	2024
Name	Plug Tag
On Metal Use	yes
Material	PC + GF
Shape	Overmolded
Key Features	Small Size, IN-Metal Use
Article Type	Special Form
Color	Black
Diameter [mm]	10
Thickness [mm]	4.5
Operating Temp °C (min)	-25
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	125
IP Class	IP68
Chemical Resistance	Not Specified

eTECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.



Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Screw/Rivet
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Туре	ISO
2024-01-267-00	M10x4.5mm	HF	MB89R118	ISO/IEC 15693 & 18000-3

eTECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.