

Transponder ON METAL Square TAG

PART ID:

2027-01-349-00

Main Specifications

Material	Polyamid		
Operating Temperature	-40°C to 60°C		
IP Class	IP68		
Compliance	RoHs & Reach, CE		
Key Features	ON-Metal Use, Rough Environment, Heat Tolerant, High Durability		
Options	Adhesive, Laser Engraving, Logo		



Chip Specification (Chip 349)

Chip	Alien - Higgs 3
Frequency	869 MHz (UHF)
Memory	TID 64 Bit; EPC 96 Bit; User 512 Bit
Norm	ISO 18000-6C / EPC Gen2 V2

Full Specifications

Product ID	2027
On Metal Use	yes
Material	Polyamid
Shape	Overmolded
Key Features	ON-Metal Use, Rough Environment, Heat Tolerant, High Durability
Options	Adhesive, Laser Engraving, Logo
Article Type	Square TAG
Color	Black
Length [mm]	51
Width [mm]	36.3
Thickness [mm]	7.5
Weight [g]	26
Hole	yes

eTECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.



Operating Temp °C (min)	-40
Operating Temp °C (max)	60
Storage Temp °C (min)	-40
Storage Temp °C (max)	60
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Screw/Rivet
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2027-01-350-00	51x36.3x7.5mm	UHF	Higgs 9	ISO 18000-6C / EPC Gen2 V2

eTECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.