

# Transponder ON METAL

## Square TAG

### PART ID:

**2029-01-349-00**

The TECTUS Square Tag is well suited to meet shipping and logistics management applications where longer read ranges and durable tags are required. The flexibility to tag both plastic and metallic surfaces in a predominant metallic environment provides the customer a one-stop solution for asset management.

### Main Specifications

Material	Polyamid
Operating Temperature	-40°C to 85°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Rough Environment, ON-Metal Use, High Durability



### Chip Specification (Chip 349)

Chip	Alien - Higgs 3
Frequency	869 MHz ( UHF )
Memory	TID 64 Bit; EPC 96 Bit; User 512 Bit
Norm	ISO 18000-6C / EPC Gen2 V2

### Full Specifications

Product ID	2029
On Metal Use	yes
Material	Polyamid
Shape	Overmolded
Long Description	The TECTUS Square Tag is well suited to meet shipping and logistics management applications where longer read ranges and durable tags are required. The flexibility to tag both plastic and metallic surfaces in a predominant metallic environment provides the customer a one-stop solution for asset management.
Key Features	Rough Environment, ON-Metal Use, High Durability
Article Type	Square TAG
Color	Black
Length [mm]	100
Width [mm]	26
Thickness [mm]	8.9

Weight [g]	17.2
Hole	yes
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	85
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Screw/Rivet
Compliance	RoHs & Reach, CE

## VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2029-01-349-00	100x26x8.9mm	UHF	Higgs 3	ISO 18000-6C / EPC Gen2 V2