

Transponder ON METAL

Square TAG

PART ID:
2055

Main Specifications

Frequencies	LF HF UHF
Material	PPS
Operating Temperature	-40°C to 85°C
IP Class	IP68
Compliance	RoHs & Reach, CE, Rain RFID
Key Features	ON-Metal Use, Rough Environment, Heat Tolerant, High Durability
Options	Laser Engraving



Full Specifications

Product ID	2055
On Metal Use	yes
Material	PPS
Shape	Overmolded
Key Features	ON-Metal Use, Rough Environment, Heat Tolerant, High Durability
Options	Laser Engraving
Article Type	Square TAG
Color	Black
Length [mm]	54
Width [mm]	36
Thickness [mm]	13
Hole	yes
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-55
Storage Temp °C (max)	150
IP Class	IP68

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Screw/Rivet
Compliance	RoHs & Reach, CE, Rain RFID

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2055-01-324-00	Black	UHF	UCODE 8	ISO 18000-6C / EPC Gen2 V2

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.