

# Transponder ON METAL

## Square TAG

**PART ID:**  
**2056**

PID 2056 features its slim shape appearance suited for narrow structure attachment. With multiple methods of fixation and durable housing, it serves well on metal surface with proven performance and has great resistibility to outdoor environmental impact. Equipped with NXP UCode 8, PID 2056 boosts a superior reading distance, making it ideal for logistics and industrial asset management purposes.

### Main Specifications

Frequencies	<b>LF HF UHF</b>
Material	Nylon Polymer
Operating Temperature	-40°C to 85°C
IP Class	IP68
Compliance	RoHs & Reach, CE, Rain RFID
Key Features	ON-Metal Use, Rough Environment, Asset Tracking, High Durability
Options	Laser Engraving



### Full Specifications

Product ID	2056
On Metal Use	yes
Material	Nylon Polymer
Shape	Overmolded
Long Description	PID 2056 features its slim shape appearance suited for narrow structure attachment. With multiple methods of fixation and durable housing, it serves well on metal surface with proven performance and has great resistibility to outdoor environmental impact. Equipped with NXP UCode 8, PID 2056 boosts a superior reading distance, making it ideal for logistics and industrial asset management purposes.
Key Features	ON-Metal Use, Rough Environment, Asset Tracking, High Durability
Options	Laser Engraving
Main Use	Logistics
Article Type	Square TAG
Color	Black
Length [mm]	78
Width [mm]	21
Thickness [mm]	11
Hole	yes

©TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	120
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Screw/Rivet
Compliance	RoHs & Reach, CE, Rain RFID

## VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2056-01-324-00	Black	UHF	UCODE 8	ISO 18000-6C / EPC Gen2 V2