Transponder ATEX/IECEx

Brick/Rod TAG

PART ID:

3007-01-327-00

ATEX Zone 1 / 21 certified UHF Mount On Metal BRICK MINI RFID TAG 32 x 13 x 5 mm

Main Specifications

Material	Nylon Polymer
Operating Temperature	-40°C to 85°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	ON-Metal Use, Rough Environment, Heat Tolerant, High Durability, Small Size

Chip Specification (Chip 327)

Chip	NXP - UCODE 9xm
Frequency	860~960 MHz (UHF)
Memory	TID 96bit ; EPC 128 bit; User 752 bit
Norm	ISO 18000-6C / EPC Gen2 V2

Full Specifications

Product ID	3007
Atex	yes
On Metal Use	yes
Material	Nylon Polymer
Shape	Overmolded
Short Description	ATEX Zone 1 / 21 certified UHF Mount On Metal BRICK MINI RFID TAG 32 x 13 x 5 mm
Long Description	The ATEX Zone 1 / 21 certified UHF Mount On Metal BRICK MINI RFID TAG 32 x 13 x 5 mm was developed to mark equipment and devices which have metallic surface and is located in hazardous areas. Despite the small shape the ATEX UHF RFID TAG is readable form a good distance by using ATEX certified stationary and protable ATEX UHF RFID readers. System integrators and users benefit of the ATEX Zone 1 / 21 certified UHF Mount On Metal BRICK MINI RFID TAG on off- and onshore oil rigs, in refineries, in chemical plants and in other application areas
Key Features	ON-Metal Use, Rough Environment, Heat Tolerant, High Durability, Small Size
Article Type	Brick/Rod TAG
Color	Black

© 2025 TECTUS Technology GmbH. All rights reserved.

The content, design, and technical data of this specification are the intellectual property of TECTUS. TECTUS reserves the right to change any information or data in this document without prior notice. TECTUS declines all responsibility for the use of products with any other specifications, but the ones mentioned above. Any additional requirement for a specific customer application must be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

TECTUS Technology GmbH | Lustheide 85 | D-51427 Bergisch Gladbach | Phone: +49 (0) 22 04 976 88 0 | Fax: +49 (0) 22 04 976 88 10

Length [mm]	31.7
Width [mm]	12.8
Thickness [mm]	4.97
Weight [g]	5
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	150
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Glue
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
3007-01-327-00	31.7x12.8x4.97mm	UHF	UCODE 9xm	ISO 18000-6C / EPC Gen2 V2

© 2025 TECTUS Technology GmbH. All rights reserved.

The content, design, and technical data of this specification are the intellectual property of TECTUS. TECTUS reserves the right to change any information or data in this document without prior notice. TECTUS declines all responsibility for the use of products with any other specifications, but the ones mentioned above. Any additional requirement for a specific customer application must be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

TECTUS Technology GmbH | Lustheide 85 | D-51427 Bergisch Gladbach | Phone: +49 (0) 22 04 976 88 0 | Fax: +49 (0) 22 04 976 88 10