

Transponder ATEX

Glass TAG

PART ID:
3017-01-112-00

ATEX Zone 1 / 21 certified 13,3 mm x 3,15 mm GLASS TAG IN METAL RFID TAG LF

Main Specifications

Material	Glass
Operating Temperature	-45°C to 60°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Small Size, ON-Metal Use, Rough Environment, Heat Tolerant, High Durability



Chip Specification (Chip 112)

Chip	NXP - HITAG S 256
Frequency	125 kHz (LF)
Memory	UID 4 Byte; User 256 Bit
Norm	ISO/IEC 11784 & 11785 & 14223

Full Specifications

Product ID	3017
Atex	yes
On Metal Use	yes
Material	Glass
Shape	Potted
Short Description	ATEX Zone 1 / 21 certified 13,3 mm x 3,15 mm GLASS TAG IN METAL RFID TAG LF
Long Description	The ATEX Zone 1 / 21 certified ATEX GLASS TAG 3,15 mm x 13,3 mm IN METAL RFID TAG LF is used for applications where an RFID TAG should be integrated into all kind of materials, including metal.
Key Features	Small Size, ON-Metal Use, Rough Environment, Heat Tolerant, High Durability
Article Type	Glass TAG
Color	Transparent
Diameter [mm]	3.2
Length [mm]	13.3
Weight [g]	0.2

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Operating Temp °C (min)	-45
Operating Temp °C (max)	60
Storage Temp °C (min)	-45
Storage Temp °C (max)	60
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Embed
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
3017-01-152-00	3.15x13.3mm	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
3017-01-112-00	3.15x13.3mm	LF	HITAG S 256	ISO/IEC 11784 & 11785 & 14223
3017-01-113-00	3.15x13.3mm	LF	HITAG S 2048	ISO/IEC 11784 & 11785 & 14223

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.