

# Transponder

## Inlay

PART ID:  
**1056**

UHF inlay has superior performance for application which requires long reading range such as access control, logistic, and asset management. Our dry inlay comes in different antenna size for selection

### Main Specifications

Frequencies	LF HF <b>UHF</b>
Material	PET
Operating Temperature	-40°C to 85°C
IP Class	Not Specified
Compliance	RoHs & Reach, CE
Key Features	Ultra Thin, Versatile, Cost-Effective



### Full Specifications

Product ID	1056
Material	PET
Shape	Inlay structure round
Long Description	UHF inlay has superior performance for application which requires long reading range such as access control, logistic, and asset management. Our dry inlay comes in different antenna size for selection
Key Features	Ultra Thin, Versatile, Cost-Effective
Main Use	Embeddable RFID
Article Type	Inlay
Diameter [mm]	18
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
IP Class	Not Specified
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Embed
Compliance	RoHs & Reach, CE

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1056-01-320-00	D18mm	UHF	UCODE G2iL / G2iL+	ISO 18000-6C / EPC Gen2 V2

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.