APOLLO PRO

RFID Reader Industry
SMART Handheld

PART ID:
4058

In the compact form of a smartphone, this device running Android has an integrated full HF Reader Modul. The APOLLO 4058 device has a powerful 1.3GHz Quad-core processor and many communication and data exchange features: 4G, Wifi, Bluetooth, GPS, 1D / 2D barcode option, NFC… The APOLLO 4058 PDA is an all-in-one tool that adapts perfectly to applications such as retail, logistics and even healthcare. With an IP65 protection grade, it is fully protected against dust and is waterproof.



Main Specifications

Frequencies	LF **HF** UHF
Material	Polyamid
Operating Temperature	-20°C to 50°C
IP Class	IP65
Compliance	RoHs & REACH, FCC, CE
Key Features	Rugged Design, 4G (LTE), Android 8.1
Options	Barcode Reader Integrated

Full Specifications

Product ID	4058
Name	APOLLO PRO
Material	Polyamid
Shape	Short Range
Long Description	In the compact form of a smartphone, this device running Android has an integrated full HF Reader Modul. The APOLLO 4058 device has a powerful 1.3GHz Quad-core processor and many communication and data exchange features: 4G, Wifi, Bluetooth, GPS, 1D / 2D barcode option, NFC… The APOLLO 4058 PDA is an all-in-one tool that adapts perfectly to applications such as retail, logistics and even healthcare. With an IP65 protection grade, it is fully protected against dust and is waterproof.
Key Features	Rugged Design, 4G (LTE), Android 8.1
Options	Barcode Reader Integrated
Article Type	SMART Handheld
Color	Black
Length [mm]	164.2

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use
of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.
Where application information is given, it is only advisory and does not form part of the specification.

TECTUS Technology GmbH | Lustheide 85 | D-51427 Bergisch Gladbach | Phone: +49 (0) 22 04 976 88 0 | Fax: +49 (0) 22 04 976 88 10

Width [mm]	78.8
Thickness [mm]	17.5
Weight [g]	321
IP Class	IP65
PCB Material	FR4
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Compliance	RoHs & REACH, FCC, CE
Read / Read Write	Read
Typical Reading Range	Short
Supported Standards / Tags	HF
Operating Temp °C (min)	-20
Operating Temp °C (max)	50
Storage Temp °C (min)	-40
Storage Temp °C (max)	60
Power Supply	Battery
Battery Type	Li-ion
Battery Capacity	5000mAh
Interfaces Physical	USB-C,SIM,SD Card
Connection	Bluetooth 4.0/WLAN/3G/4G/GPS
Operating System	Android 8.1
Display Size	5.2
Touch Display	Yes
Camera	13MP/5MP
GPS	Yes
Integrated Bar Code Scanner	Optional
Memory Type	RAM/ROM
Memory Capacity	2GB/16GB
Memory Card Slot	yes
CPU	Cortex-A53 Quad-Core 1..3MHz
Display Resolution	1920x1080P
Keyboard	4 Buttons
Integrated RFID Reader	Full HF

VARIANTS

ID	Variant
4058-01-000-00	Handheld Full HF

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use
of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.
Where application information is given, it is only advisory and does not form part of the specification.

TECTUS Technology GmbH | Lustheide 85 | D-51427 Bergisch Gladbach | Phone: +49 (0) 22 04 976 88 0 | Fax: +49 (0) 22 04 976 88 10