

SEAL TAG

Transponder
Special Form

PART ID:

1036-01-260-00

RFID Tags with integrated fasteners prevent tampering with the contents of sealed containers.

Main Specifications

Material	PC
Operating Temperature	-40°C to 85°C
IP Class	Not Specified
Compliance	RoHs & Reach, CE
Key Features	Tamper Evident, Versatile, High Durability
Options	Laser Engraving, Barcode, Offset Print, UID Printing



Chip Specification (Chip 260)

Chip	NXP - ICODE SLIX
Frequency	13.56 MHz (HF)
Memory	UID 8 Byte; User 1024 Bit
Norm	ISO/IEC 15693 & 18000-3

Full Specifications

Product ID	1036
Name	SEAL TAG
Material	PC
Shape	Ultrasonic Welded
Short Description	RFID Tags with integrated fasteners prevent tampering with the contents of sealed containers.
Long Description	Seal Tag eTamper are passive contactless HF/NFC-V transponders that stop working when the sealing wire loop is broken, making tampering evident via RFID. Whenever it is important to authenticate an item the tag has been affixed to, or ensure a compartment has not been opened since the time of sealing, these tags should be applied.
Key Features	Tamper Evident, Versatile, High Durability
Options	Laser Engraving, Barcode, Offset Print, UID Printing
Main Use	Asset Tracking
Article Type	Special Form
Color	White

©TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.

Length [mm]	23
Width [mm]	18
Thickness [mm]	3
Weight [g]	1
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	90
IP Class	Not Specified
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Cable tie
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1036-01-260-00	17.5x27x3.3mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3