

Transponder

Laundry TAG

PART ID:
1064

Pliable RFID Tags mount anywhere and endure rugged conditions.

Main Specifications

Frequencies	LF HF UHF
Material	TPE
Operating Temperature	-40°C to 85°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Rough Environment, Heat Tolerant, High Durability
Options	Laser Engraving



Full Specifications

Product ID	1064
Material	TPE
Shape	Overmolded
Long Description	Pliable RFID Tags mount anywhere and endure rugged conditions.
Key Features	Rough Environment, Heat Tolerant, High Durability
Options	Laser Engraving
Main Use	Commercial Laundry
Article Type	Laundry TAG
Color	White
Length [mm]	55
Width [mm]	12
Thickness [mm]	2.2
Weight [g]	1.4
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	85

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Peak Temp I / °C	120
Peak TIME I [h]	72
High Temp	yes
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	IK 06
Attachment Method	Sew-in
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1064-01-349-00	55x12x2.2mm, White	UHF	Higgs 3	ISO 18000-6C / EPC Gen2 V2

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.